



Natural



Antiqued



Sanded



Leather



Honed



Paving



Walling



Coping



Steps



Setts



Kerbs

Defined by its calm blue-grey tone and finely layered structure, Twilight Flow combines refined aesthetics with dependable durability. Its compact grain and subtle surface texture make it a suitable choice for architectural and landscape design, maintaining elegance through years of exposure and use.

- ✓ Compressive integrity ensures it performs in load-bearing and decorative applications
- ✓ Dense and low-porosity composition resists moisture ingress and environmental wear
- ✓ Flexural stability provides lasting reliability in paving, walling, and façade installations

Physical Properties	Mechanical Strength
Apparent Density (kg/m ³)	2,700
Water Absorption (%)	upto 0.1
Compressive Strength (MPa)	120 – 230
Flexural Strength (MPa)	13 – 25

Dimensions, thicknesses, and configurations of slabs can be customised in accordance with specific project or client requirements. Technical data sheets, quality certifications, and laboratory test reports can be furnished upon request or as required by the project specifications. Images are digitally created for representational purposes to convey tone and character; natural stone may vary in colour and pattern.

T: +91 82 9178 8999

E: contactus@stoneshippers.com

W: www.stonestry.com

All product descriptions, images, and specifications are provided for general information and illustrative purposes only. Natural stone is a product of nature; variations in colour, texture, and veining are inherent and should be expected. While every effort is made to ensure accuracy, the actual material may differ slightly from samples or photographs. Performance characteristics, such as durability and slip resistance, may vary depending on installation, finish, and maintenance. The company reserves the right to change product information without prior notice.